

Excellent Business

# NR-300/NR-400

Upgraded performance and newly designed ECR

Trendy and compact design for small business  
User-friendly functions

- / Powerful user interface
- / Various options supported
- / Built-in power battery



Wide graphic LCD for user (NR-400)



2 1/2" Thermal Printer



GPRS modem (Option)



Back-up sales data to SD card



Possible to change keyboard button menu (Option)

# NR-300/NR-400

The new ECR with contemporary and special design

## Small and Modern Design

- Luxurious and stylish design
- Space saving design for small shop owners
- Luxurious blue color back-Light
- Elegant body color

## Reliable System

- Superb performance on small size
- Back-up sales data to USB memory
- Built-in power battery(operates for up to 8 hours)
- Long life span thermal printer

## User-Friendly Function

- Wide graphic LCD (NR-400)
- Programmable raised keys with caps (Option)

## Powerful Interface

- Built in GPRS modem (Quad band)
- USB host and device (Default)
- Back-up sales data to SD card
- Variety of interface options(Ethernet, RS-232C, Cash drawer, etc)



User interface part



NR-300/NR-400 is a smart electronic cash register with powerful performance and compact design for the small business.



Items		NR-300/NR-400
System	CPU	R X 631 [RENESAS, 32bit]
	PGM MEMORY	2Mbyte FLASH [CPU internal]
	DATA MEMORY	Max 8Mbit SRAM
	FISCAL MEMORY	4Mbit OTPROM
Display	FRONT	NR-300 : 16char X 2line LCD with BLUE B/L NR-400 : 192 X 64 graphic LCD with BLUE B/L
	REAR	16char X 2line LCD with BLUE B/L
Interface	SERIAL	RS-232C X 2-port [RJ45 X 2]
	USB	Host: 1-port (for F/W upgrade and save report)
		Device: 1-port (for connecting PC)
		Host / Device functions are selectable by software (PORT PROGRAM)
	SD CARD	2-slot (internal Micro SD 1-slot, external Normal SD 1-slot) SDHC compatible
	GPRS MODEM	Built-in [SIERRA Q2687, Quad band]
	ETHERNET	TCP/IP, 10/100Base-T
Appearance	DRAWER	1-port with RJ-11 [24V]
	DIMENSION	259(W) X 210(D) X 86(H)
	WEIGHT	Approx. 2Kg
Printer	TYPE	2"/3" THERMAL
	SPEED	70mm/s_max
Power	ADAPTER(External)	DC9V/2.5A
	BATTERY(Internal)	DC 6V/3.2A (LEAD-ACID)
Option		SD Card, Ethernet, GPRS (built-in)